



PCB LAYOUT

备注：侧弹分为外弹与内弹

目錄 MAPX	變更內容 MODIFICATION	日期 DATE

- NOTES:
- Housing: Thermoplastics, UL94V-0
  - Contact: Copper Alloy
  - Shell: Copper Alloy/Steel
  - Voltage Current Rating: 1.5 AMP. 30V AC
  - Insulation Resistance: 1000MΩ Min.
  - Contact Resistance: 30 MΩ Max.
  - Dielectric Withstanding Voltage: 500W AC
  - Temperature Range: -35°C to +85°C
  - Insulator color: Black/White
  - Plastic material: PBT/LCP/Others
  - Shell finish: Nickel plated/Tin-Lead plated
  - Mechanical:
    - Mating Force: 3.5KG MAX
    - Umating Force: 0.7 KG MIN.
  - Contact finish:
    - 01: Selective Gold Flash
    - 02: Selective Gold 3U”
    - 03: Selective Gold 5U”
    - 04: Selective Gold 15U”
    - 05: Selective Gold 30U”

产品图  
PRODUCT CHART DWG

深圳市精拓金电子有限公司

公差一览表 TOLERANCE UNLESS OTHERWISE		单位 UNITS	制图 DRAWING	产品料号 PRODUCT PART NO.
X	±0.25	X	Z-Y-B	903-241A1021D10100
X	±0.20	X	审核 CHD	AF90度无后盖直脚无边内弹铁壳 T型PBT黑胶
XX	±0.15	XX	核准 APPD	雷永键
.XXX	±0.10	.XXX	日期 DATE	2009/10/20
			角法 VIEW	版本 VERS