



MAPX	MODIFICATION	DATE
------	--------------	------

Specifications:
Electrical:
 1.Current Rating :1.5A/contact terminal
 2.Voltage Rating :30V DC
 3.Contact Resistance:30 milliohms MAX
 4.Dielectric Withstanding Voitage:500 V AC AT Sea Level
 5.Insulation Resistance:1000MEGA ohms MIN
Mechanical:
 1.Connector Mate and Unmate Force: Mate force:3.75kgf(MAX)
 Unmate force:0.40kgf(MIN)
 2.Terminal Retention :0.40kgf(MIN)
Material:
 1.Housing: Hing Temperature Ternmaplastics,
 UI 94V-0 LCP White/Black
 2.Contact:Copper Alloy C2680
 3.Shell: Copper Alloy C2680/SPCC
Finish:
 1.Contact: Plated Gold in Mating Area; Tin On Solder Talls
 2.Shell: Nickel Plating

产品图 PRODUCT CHART DWG 公差一览表 TOLERANCE UNLESS OTHERWISE				深圳市精拓金电子有限公司						
X.	±0.35	X.	±5.°	单位	MM	制图	Gavin	制图料号	920-462A2021Y10103	
.X	±0.30	.X	±2.°	比例	1:1	审核	郭治富	产品名称	MINI/5P 母座立式6.65/7.7无边两脚	
.XX	±0.20	.XX	±1.°	日期	2016-09-09	核准	黄国荣	角法	全贴片LCP 黑胶端子SMT	
.XXX	±0.10	.XXX	±0.5°	DATE		APPD		VIEW	版本	AD