




目錄 MAPX	設 變 內 容 MODIFICATION	日 期 DATE

NOTES:

Housing: Thermoplastics,UL94V-0

Contact: Copper Alloy

Shell: Copper Alloy/Steel

Voltage Current Rating:1.5 AMP. 30V AC

Insulation Resistance:1000MΩ Min.

Contact Resistance:30 MΩ Max.

Dielectric Withstanding Voltage:500W AC

Temperature Range:-35℃ to +85℃

Insulator color: Black/White

Plastic material:PBT/LCP/Others

Shell finish:Nickel plated/Tin-Lead plated

Mechanical:

Mating Force:3.5KG MAX

Unmating Force:0.7 KG MIN.

Contact finish:

01:Selective Gold Flash

02:Selective Gold 3U"

03:Selective Gold 5U"

04:Selective Gold 15U"

05:Selective Gold 30U"

产 品 图 PRODUCT CHART DWG				深 圳 市 精 拓 金 电 子 有 限 公 司			
公差一览表 TOLERANCE UNLESS OTHERWISE				单位 UNITS	MM	制图 DRAWING	Z-Y-B
X.	±0.25	X'.	±5°	比例 SCALE	1:1	审核 CHKD	产品料号 PRODUCT PART NO.
.XX	±0.20	.XX'	±2°	日期 DATE	2015. 03. 14	核准 APPD	产品名称 PRODUCT NO.
.XX	±0.15	.XX'	±1°				角法 VIEW
.XXX	±0.10	.XXX'	±0.5°				版本 VER
							核 准 A0