




Note:
1.Material:
1.1 Housing: High temperature thermoplastic with g.f,UL94v-0
1.2 Contact: copper alloy,t=0.20mm
1.3 Shell: copper alloy,t=0.25mm
2.Specification:
2.1 Current rating:1,5PIN 1.8A Max/2,3,4PIN 1A Max.
2.2 Dielectric withstanding voltage: 100 V(ac) for 1 min.
2.3 Contact resistance: 30 mΩ Max.
2.4 Insulation resistance: 100 MΩ Min.
2.5 Total mating force: 3.57 Kg Max.
2.6 Total unmating force: 1.0 Kg Min
2.7 Temperature range: -30°C~80°C

产品图 PRODUCT CHART DWG				深圳市精拓金电子有限公司							
公差一览表 TOLERANCE UNLESS OTHERWISE				单位 UNITS	MM	制图 DRAWING	尹先华	制图料号 DRAWING PART NO.	920-D62A2021S10105		
X.	±0.30	X.	±5.°	比例 SCALE	1:1	审核 CHKD	郭治富	产品名称 PRODUCT NO.	MICRO 5P-F B型两脚贴板无卷边有柱LCP		
.X	±0.25	.X	±2.°						黑胶卷带成品		
.XX	±0.15	.XX	±1.°	日期 DATE	2021-04-16	核准 APPD	黄国荣	角法 VIEW		版本 VER	AO
.XXX	±0.10	.XXX	±0.5°								