








NOTE:

1. Material:

Housing: Thermoplastics, UL94V-0 (ROHS, HF)
Contact: Phosphor Bronze C5191-EH/C2680-EH, T=0.25mm
Shell: COPPER ALLOY T=0.30mm

2. FINISH:

Contact: 15u" Gold Plated on Contact Area,
80u" Min. Tin Plated on Solder Area
50u" Min. Nickel Underplating Over All.
Shell: 50u" Min. Nickel Underplating Over All.

3. Specification:

3.1: Rating:

Rated voltage 500V AC/DC. Rated current: 2 A Max.

3.2: Electrical:

Insulation Resistance(EIA-364-21):
1000MΩ Min. at 500V/DC for 1Minute.

Contact Resistance(EIA-364-23):
30 mΩ Max. at 20mV Max, 50mA

Dielectric Withstanding Voltage(EIA-364-20):

No discharge, flashover or breakdown at 500V/AC 1Minute

4. Plug extraction force shall be between 1.0kgf and 2.00kgf

5. Contact finish:

- 01: Selective Gold Flash
- 02: Selective Gold 1U"
- 03: Selective Gold 3U"
- 04: Selective Gold 5U"
- 05: Selective Gold 15U"
- 06: Selective Gold 30U"

产品图				深圳市精拓金电子有限公司						
PRODUCT CHART DWG										
公差一览表										
TOLERANCE UNLESS OTHERWISE				单位	MM	制图	Z-Y-B	制图料号	906-451A1021D10200	
X	±0.25	X	±5.°	UNITS		DRAWING		PRODUCT PART NO		
.X	±0.20	.X	±2.°	比例	1:1	审核		产品名称	AF14. 0侧插短体外弯内0型脚有边	
.XX	±0.15	.XX	±1.°	SCALE		CHKD		PRODUCT NO	铁壳PBT黑胶	
.XXX	±0.10	.XXX	±0.5°	日期	2013.12.20	核准		角法	版本	AO
				DATE		APPD		VIEW	REV	